

3.バックナーのサイズ

バックナーの寸法は、下表の通りとなっております。但し下表以外の寸法も対応致しますので、ご相談ください。

(単位:mm)

直径 容積(ℓ)	600	700	800	900	1,000	1,050	1,100	1,150	1,200	1,300	1,400
300	1,060	780									
400	1,420	1,040	800								
500		1,300	1,000								
600			1,200								
700			1,400	1,100							
800				1,260	1,020		(高さ)				
900				1,420	1,150	1,040					
1,000				1,570	1,270	1,160	1,050				
1,100					1,400	1,270	1,160	1,060			
1,200					1,530	1,390	1,270	1,160	1,070		
1,300					1,660	1,500	1,370	1,260	1,150		
1,400					1,790	1,620	1,480	1,350	1,240	1,060	
1,500					1,910	1,740	1,580	1,450	1,330	1,130	
1,600						1,850	1,690	1,550	1,420	1,210	1,040
1,700						1,970	1,790	1,640	1,510	1,280	1,110
1,800						2,080	1,900	1,740	1,600	1,360	1,170
1,900							2,000	1,840	1,680	1,430	1,240
2,000							2,100	1,930	1,770	1,510	1,300
2,100								2,030	1,860	1,580	1,370
2,200									1,950	1,660	1,430
2,300									2,040	1,740	1,500
2,400										1,810	1,560
2,500											1,630

●バックナーの寸法はJIS規格「JIS Z 1651」によって制定されております。

- バックナーの高さは直径の2倍を超えない。
- バックナーの寸法の許容差は、直径は±2%、高さは±3%。